

1. PRODUCT NAME

BX-043
Concrete Joint Sealant / Waterstop Tape

2. MANUFACTURER

H.B. Fuller
4401 Page Avenue, Michigan Center, MI 49254 U.S.A.
Phone 800.248.4010 | Fax 517.764.6697 | hbfuller.com

3. DESCRIPTION

BX-043 is a flexible concrete construction joint sealant tape that provides a positive seal by expanding upon contact with moisture. BX-043 is a special blend of butyl rubber polymers and bentonite clay that provides superior expansion characteristics in concrete joints.

Basic Use

BX-043 is designed to be used in non-moving concrete joints and is ideal for most below grade precast and cast-in-place joints.

Typical Applications

- Foundation slabs
- Below grade walls

Key Features and Benefits

- Easy to apply tape form
- Remains flexible in cold weather

Suitable Substrates

- Concrete
- Metal

Application Instructions

- Apply to clean, dry surfaces.
- Do not apply to wet surfaces or allow exposure to water prior to application.
- BP-013 primer recommended for vertical application.
- Brush to remove all loose debris from concrete surface.
- For best adhesion press firmly to surface.
- Press tape ends firmly together to create a continuous seal.
- Remove release liner prior to concrete pour.

Storage

Store material in original unopened container between -23°C and 32°C (-10°F and 90°F).

Shelf Life

Minimum 2 years from date of manufacture when stored as recommended.

Limitations

- Designed for non-moving joints
- Not intended for expansion joints

4. PACKAGING

BX-043 is available in pre-extruded tape form in various custom profiles. Please inquire about your specific needs.

Standard Profiles & Sizes



Trapezoid



Rectangular

3/4" x 1"	Rectangular	16'8" roll
1/2" x 0.67" x 1-1/4"	Trapezoid	20' roll



5. AVAILABILITY

Please contact your local Sales Representative to discuss your specific needs.

6. TECHNICAL SERVICES

Prior to working with this or any product, consult product label and Safety Data Sheet (SDS) for necessary health and safety precautions.

7. TECHNICAL DATA

Property	Typical Value	Test Method
Color	Black	Visual
Specific Gravity	1.60	ASTM D71
Hardness	75 dmm	ASTM D217
Solids Content	100%	ASTM C681
Unrestricted Swell	300%	

Application Properties

Application Temperature	12°C to 32°C (-10°F to 90°F)
Service Temperature	-45°C to 54°C (-50°F to 130°F)

NOTE: The foregoing information is published as general information only. The listed properties and performance characteristics are approximate values and are not to be interpreted as manufacturing specifications



For more information contact:
CUSTOMER SERVICE

H.B. Fuller
4401 Page Ave, Michigan Center, MI 49254
P: +1 517-764-0334 | hbfuller.com

IMPORTANT - Information, specifications, procedures and recommendations provided are based on our experience, and we believe this information to be accurate. No representation guarantee or warranty is made as to the accuracy or completeness of the information or that use of the product will avoid losses or damages or give desired results. It is purchaser's sole responsibility to test and determine the suitability of any product for the intended use. Tests should be repeated if materials or conditions change in any way. No employee, distributor or agent has any right to change these facts and offer a guarantee of performance.

NOTE TO USER - By ordering/receiving product you accept the H.B. Fuller General Terms and Conditions of Sale applicable in the region. Please request a copy if you have not received these. These Terms and Conditions contain disclaimers of implied warranties (including but not limited to disclaiming warranties of fitness for a particular purpose) and limits of liability. All other terms are rejected. In any event, the total aggregate liability of H.B. Fuller for any claim or series of related claims, however arising, in contract, tort (including negligence), breach of statutory duty, misrepresentation, strict liability or otherwise is limited to replacement of affected products or refund of the purchase price for affected products. H.B. Fuller shall not be liable for loss of profit, loss of margin, loss of contract, loss of business, loss of goodwill or any indirect or consequential losses arising out of or in connection with product supply.

To learn more, visit hbfuller.com

